



## Depth Gauge - M0084



- nominal size: 150
- antimagnetic, maintenance-free
- shock and vibration resistant
- on shock absorbers
- rear mounting rim
- with venting screw

Applications shipbuilding, naval shipbuilding

Media water, sea water

Available Versions			
measuring element	bourdon tube		
process connection	G1/2"A M20x1,5 M16x1,5 Minimes		
connection position	bottom, 270° (right) *other positions on request		
accuracy class:	0,6 as per DIN EN 837-1 1 as per DIN EN 837-1		
weather protection	IP 54 as per DIN EN 60529		
short term overpressure	130% of scale		
Technical Limitations			
operation temperature	min	-20°C	max +50°C
temperature influence			±0,4% FSO / 10K
weight		3,5kg	
Material			
casing	aluminium		
wetted parts	copper alloy		
window	safety glass		
Colours			
casing	black	RAL 9005	
	grey	RAL 7037	
scale background	white	RAL 9010	
	black	RAL 9005	
	fluorescent	UVG 75 green	
scale labels	yellow	RAL 1021	
	fluorescent	UVG 75 green	
pointer	black	RAL 9005	
	black	RAL 9005	
	yellow	RAL 1021	
	fluorescent	UVG 75 green	
	*other colour options on enquiry		

