



Bestellschlüssel LVL 901 Order Key LVL 901

| Messgröße / unit of measurement | | | |
|--|-------|-------|---------|
| bar, relativ bar, relative | | 1 | |
| bar, absolut bar, absolute | | 2 | |
| mWS, relativ mWS, relative | | 3 | |
| Messbereich / measure range | | | |
| | [mWS] | [bar] | |
| | 0,4 | 0,04 | 0 4 0 0 |
| | 0,6 | 0,06 | 0 6 0 0 |
| | 1,0 | 0,10 | 1 0 0 0 |
| | 1,6 | 0,16 | 1 6 0 0 |
| | 2,5 | 0,25 | 2 5 0 0 |
| | 4,0 | 0,40 | 4 0 0 0 |
| | 6,0 | 0,60 | 6 0 0 0 |
| | 10,0 | 1,00 | 1 0 0 1 |
| | 16,0 | 1,60 | 1 6 0 1 |
| | 25,0 | 2,50 | 2 5 0 1 |
| | 40,0 | 4,00 | 4 0 0 1 |
| | 50,0 | 5,00 | 5 0 0 1 |
| Sondermessbereiche / non-standard ranges | | | 9 9 9 9 |
| Gehäusematerial / material of casing | | | |
| Edelstahl 1.4404 / stainless steel 1.4404 | | | 1 |
| CuNi10Fe1Mn | | | K |
| Gehäuseform / type of casing | | | |
| Tauchsonde 40mm / 40mm submerged sensor | | | T 0 0 |
| Tauchsonde 54mm / 54mm submerged sensor | | | T 0 1 |
| Tauchsonde 70mm / 70mm submerged sensor | | | T 0 2 |
| Flanschsonde / flange sensor | | | F 0 0 |
| Ex-Schutz / explosion protection | | | |
| ohne / none | | | 1 |
| Zone 0 II 1G Ex ia IIB T4 Ga | | | E |
| Genauigkeit / accuracy | | | |
| 0,25 % | | | 2 |
| 0,10 % | | | 1 |
| Kabellänge / cable length | | | |
| in m | | | 9 9 9 |
| Sonderausführungen / special variants | | | |
| Standard | | | 0 |
| Pt100 | | | 1 |